

FEATURES

- Maximum flow rate of 2.5 gpm (9.5 lpm)
- 11" diameter spray face
- Single spray showerhead
- Rubber nozzles to prevent limescale build up
- Includes shower arm and escutcheon
- 1/2" NPT connection

COLORS/FINISHES

- #CP Polished Chrome
- #BN Brushed Nickel
- #PN Polished Nickel
- #RB Oil Rubbed Bronze



CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



PRODUCT SPECIFICATION

The showerhead shall have a maximum flow rate of 2.5 gpm (9.5 lpm). Product shall have a 11" diameter spray face. Product shall have a single spray. Product shall have rubber nozzles to prevent limescale build up. Product shall include shower arm and escutcheon. Product shall be TOTO Model TS100B#_____.

SPECIFICATIONS

- Warranty: Lifetime Limited Warranty (Residential Use)
One Year (Oil Rubbed Bronze)
One Year (Commercial Use)
- Material: Brass
- Shipping Weight: 12.0 lbs.
- Shipping Dimensions: 21-1/2" L x 14-1/4" W x 3-1/4" H
- Maximum Flow Rate: 2.5 gpm (9.5 lpm)

